



## KHX13000D3LLK2/2GN

**2GB (1GB 128M x 64-Bit x 2 pcs.) PC3-13000**  
**CL8 240-Pin DIMM Kit**

### DESCRIPTION:


Kingston's KHX13000D3LLK2/2GN is a kit of two 128M x 64-bit 1GB (1024MB) DDR3-1625 CL8 SDRAM (Synchronous DRAM) "NVIDIA SLI-Ready" memory modules, based on eight 128M x 8-bit DDR3 FBGA components. Total kit capacity is 2GB (2048MB). Each module pair has been tested to run at DDR3-1625MHz at a low latency timing of 8-7-7 at 1.8V. The SPDs are programmed to JEDEC standard latency DDR3-1066Mhz timing of 7-7-7 at 1.5V. Each 240-pin DIMM uses gold contact fingers and requires +1.5V. The JEDEC standard electrical and mechanical specifications are as follows:

### FEATURES:

- JEDEC standard 1.5V  $\pm$  0.075V Power Supply
- VDDQ = 1.5V  $\pm$  0.075V
- 533MHz fCK for 1066Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 5,6,7,8,9,10
- Posted CAS
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- Programmable CAS Write Latency(CWL) = 7(DDR3-1066)
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm  $\pm$  1%)
- On Die Termination using ODT pin
- Average Refresh Period 7.8us at lower then TCASE 85°C, 3.9us at 85°C < TCASE . 95°C
- Asynchronous Reset
- 1066Mbps CL7 doesn't have backward compatibility with 800Mbps CL5
- PCB : Height 1.180" (30.00mm), single sided component

### PERFORMANCE:

- |  |                              |
|--|------------------------------|
| <input checked="" type="checkbox"/> CL(IDD)  | 7 cycles                     |
| <input checked="" type="checkbox"/> Row Cycle Time (tRCmin)                          | 50.63ns (min.)               |
| <input checked="" type="checkbox"/> Refresh to Active/Refresh Command Time (tRFCmin) | 110ns                        |
| <input checked="" type="checkbox"/> Row Active Time (tRASmin)                        | 37.5ns (min.)                |
| <input checked="" type="checkbox"/> Power  | TBD W (operating per module) |
| <input checked="" type="checkbox"/> UL Rating  | 94 V - 0                     |
| <input checked="" type="checkbox"/> Operating Temperature                            | 0° C to 85° C                |
| <input checked="" type="checkbox"/> Storage Temperature                              | -55° C to +100° C            |



**MODULE DIMENSIONS:**

